

Cessna 172 Checklist

Dayton Aviation Services, LLC

<u>PREFLIGHT INSPECTION CABIN</u>	
1) A.R.O.W.	LOCATE
2) Hobbs/Tach Time	RECORD
3) Parking Brake	SET
4) Control Wheel Lock	REMOVE; CHECK
5) Ignition Switch	OFF
6) Avionics	OFF
7) Master Switch	ON
8) Fuel	CHECK QUANTITY
9) Flaps	LOWER
10) Lights	CHECK
11) Master Switch	OFF
12) Alternate Static Air	OFF
13) Fuel Selector	BOTH
14) Fuel Tester and Dipstick	OBTAIN

<u>EXTERIOR INSPECTION</u>	
FUSELAGE/EMPENNAGE	
1) Body Surface	CHECK
2) Baggage Door	SECURED & LOCKED
3) Control Surfaces	FREE and CORRECT
4) Tail Tie Down	REMOVE

<u>RIGHT WING</u>	
1) Flap & Aileron	CHECK
2) Wing	CHECK
3) Wing Tie Down	REMOVE
4) Wheel Assembly	CHECK
5) Fuel	DRAIN
6) Fuel Quantity	CHECK VISUAL
7) Fuel Filler Cap	SECURE

<u>NOSE</u>	
1) Cowling	SECURE
2) Oil Quantity	5-6 Qts; Record
3) Fuel Strainer	DRAIN
4) Propeller and Spinner	CHECK
5) Air Inlets	REMOVE PLUGS; CLEAR
6) Carburetor Air Filter	CHECK
7) Nose Strut and Wheel	CHECK
8) Static Port	CLEAR
9) Windshield	CLEAR

<u>LEFT WING</u>	
1) Pitot Tube	REMOVE COVER; CHECK
2) Fuel Tank Vent	CHECK
3) Wing	CHECK
4) Wing Tie Down	REMOVE
5) Flap & Aileron	CHECK
6) Wheel Assembly	CHECK
7) Fuel	DRAIN
8) Fuel Quantity	CHECK VISUAL
9) Fuel Filler Cap	SECURE

<u>BEFORE STARTING ENGINE</u>	
1) Exterior Preflight	COMPLETE
2) Brakes	TEST and SET
3) Passenger Briefing	COMPLETE
4) Seats, Belts, Harnesses	ADJUST and LOCK
5) Radio Master, Autopilot	OFF
6) Electrical Equipment	OFF

<u>STARTING ENGINE</u>	
1) Fuel Selector Valve	BOTH (or START)
2) Trim Tab	Set for TAKE-OFF
3) Mixture	RICH (below 3000 ft.)
4) Throttle	OPEN 1/4 INCH
5) Carburetor Heat	COLD
6) Rotating Beacon	ON
7) Circuit Breakers	CHECK
8) Ignition Switch	OFF
9) Prime	AS REQUIRED (MAX 2)
10) Master Switch	ON
11) Propeller Area	CLEAR
12) Ignition Switch	START; Then Release
13) Oil Pressure	CHECK
14) Throttle	ADJUST (800-1000 RPM)

<u>BEFORE TAXI</u>	
1) Flaps	RETRACT
2) Mixture	LEAN for Taxi
3) Throttle	1000 RPM
4) Radio Master	ON
5) Transponder	Set to ALT and SQUAWK
6) Radios & Instruments	SET
7) Weather	LISTEN
8) Nav Lights (ADS-B)	ON

<u>ENGINE RUN-UP</u>	
1) Brakes	SET
2) Flight Controls	FREE and CORRECT
3) Lights	AS REQUIRED
4) Fuel Selector	BOTH (or START)
5) Mixture	RICH (below 3000 ft.)
6) Throttle	1700 RPM
a. Carburetor Heat	CHECK (for RPM drop)
b. Magnetos	CHECK DROP
<i>(<125 RPM and <50 RPM difference)</i>	
c. Engine Instruments	CHECK
d. Vacuum (If Installed)	CHECK
e. Throttle to Idle	CHECK
<i>(then back to 1000 RPM)</i>	

<u>BEFORE TAKE-OFF</u>	
1) Friction Lock	ADJUST
2) Flight Instruments and Radios	SET
3) Autopilot (If Installed)	OFF
4) Doors and Windows	CLOSED and LOCKED
5) Seats, Belts, Harness	SECURED

<u>TAKE - OFF</u>	
<i>Normal Take-Off</i>	
1) Wing Flaps	SET
2) Carburetor Heat	COLD
3) Transponder	ALT and SQUAWK
4) Throttle	1500 RPM
5) Engine Instrument Ammeter, Vacuum	GREEN
6) Throttle	FULL
7) Rotate	52 KTS (60 MPH)
8) Climb Speed	65(75) to 74(85)

<u>Maximum Performance Take-Off</u>	
1) Wing Flaps	SET
2) Carburetor Heat	COLD
3) Lights	AS REQUIRED
4) Transponder	ALT and SQUAWK
5) Brakes	APPLY
6) Throttle	1500 RPM
7) Engine Instruments, Ammeter, Vacuum	GREEN
8) Throttle	FULL
9) Rotate	55 KTS (60 MPH)
10) Climb Speed	65(75) to 74(85)

<u>ENROUTE CLIMB</u>	
1) Airspeed	70(80) to 78(90)
2) Throttle	FULL
3) Mixture	FULL RICH

<u>CRUISE</u>	
1) Power	2200 to 2700 RPM (no more than 75%)
2) Trim	ADJUST
3) Mixture	LEAN

<u>LET-DOWN</u>	
1) Mixture	RICH
2) Power	AS DESIRED
3) Carburetor Heat	AS REQUIRED

<u>BEFORE LANDING</u>	
1) Fuel Selector	BOTH
2) Mixture	RICH
3) Carburetor Heat	ON
4) Airspeed	60 KTS(70 MPH) to 70(80)
5) Lights	AS REQUIRED
6) Wing Flaps	AS DESIRED
7) Short Final Airspeed	55(65) to 65(75)

<u>BALKED LANDING/ GO AROUND</u>	
1) Throttle and Carb Heat	FULL FWD; COLD
2) Wing Flaps	20°
3) Airspeed	55 KTS (65 MPH)
4) Wing Flaps	RETRACT SLOWLY

<u>NORMAL LANDING</u>	
1) Touchdown	MAIN WHEELS FIRST
2) Landing Roll	LOWER NOSE GENTLY
3) Braking	MINIMUM REQUIRED

<u>AFTER LANDING</u>	
1) Wing Flaps	UP
2) Carburetor Heat	COLD
3) Landing Light	OFF

<u>ENGINE SHUTDOWN & SECURING</u>	
1) Avionics Switch	OFF
2) Throttle	1000 RPM
3) Mixture	IDLE CUT-OFF
4) Ignition Switch	OFF
5) Master Switch	OFF
6) Hobbs and Tach	RECORD
7) Control Lock, Belts, Tiedowns	SECURE

<u>EMERGENCY PROCEDURES</u>	
ENGINE FAILURE AFTER TAKE-OFF	
1) Airspeed	65 KTS (75 MPH)
[flaps DOWN]	61 KTS (70 MPH)
2) Mixture	IDLE CUT-OFF
3) Fuel Selector	OFF
4) Ignition Switch	OFF
5) Wing Flaps	AS REQUIRED (40°)
6) Master Switch	OFF

<u>ENGINE FAILURE DURING FLIGHT</u>	
1) BEST GLIDE	70 KTS (80 MPH)
2) Fuel Selector	BOTH (or START)
3) Mixture	RICH
4) Carburetor Heat	ON
5) Ignition Switch	BOTH (or START)
6) Primer	IN and LOCKED

<u>ENGINE FIRE IN FLIGHT</u>	
1) Mixture	IDLE CUT OFF
2) Fuel Selector	OFF
3) Master Switch	OFF
4) Cabin Heat & Air	OFF
5) Airspeed	87KTS (100MPH)
IF NOT EXTINGUISHED, INCREASE GLIDESPEED AND FIND AIRSPEED TO PROVIDE INCOMBUSTBALE MIXTURE	
6) Forced Landing	EXECUTE

DAYTON AVIATION SERVICES, LLC
 3800 CLEARVIEW RD
 DAYTON, OH 45439
 (937) 372-2460
 DaytonAviation.com